



#### EagleEyes for Mobile Surveillance

Official Website : www.eagleeyescctv.com Video Demo : www.eagleeyescctv.com/video Technical Support : support@eagleeyescctv.com

# AVN211 / 211V

# **H.264 Network Camera**



### FEATURES

- Powerful Remote Surveillance on Multiple Mobile Platforms
  - -- For mobile device platforms, iPad®, iPod®, iPhone®, BlackBerry®, Nokia® Symbian, Windows® Mobile & Android™ (with their built-in web browsers or EagleEyes)
  - -- For web browsers, Internet Explorer®, Mozilla Firefox®, Apple® Safari®, Google Chrome™ and Opera
  - -- For operating systems, Windows & Mac
  - -- For multiple device control, our CMS software, Video Viewer, is provided for free
- Low-latency video streaming with H.264 compression format for sharp and clear images
- Hybrid digital / analog video output
- It is friendly to use by wizard with browser
- Motion detection
- Free CMS software with E-Map for multiple devices control & surveillance
- (AVN211V Only) ONVIF standard supported to simplify system integration

#### • SPECIFICATIONS

	AVN211	AVN211V	
Network			
LAN Port	YES		
LAN Speed	10/100 Based-T Ethernet		
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP, IPv4, Bonjour, UPnP, DNS, UDP		
ONVIF Support	NO	YES	
Frame Rate	NTSC:30, PAL:25		
Number of Online Users	10		
Security	Multiple user access levels with password / IP address filtering		
Web management	(1) The licensed software "Video Viewer" for up to 16 network cameras control simultaneously		
	(2) AJAX management us	er interface for web browser	
Video			
Video Compression	H.264 / MPEG4 / MJPEG		
Video Remote Control	YES		
Video Adjustment	Brightness, Contrast, Saturation and Hue		
Mobile	Supports 3GPP mobile surveillance		



#### **SPECIFICATIONS (CONTINUED...)** lacksquare

	AVN211	AVN211V	
Camera			
Image Sensor	1/3" H.R. CCD image sensor		
Pixels	768(H) x 494(V) <ntsc> / 752(H) x 582(V) <pal></pal></ntsc>		
Lens	f4.6mm		
F-number	F1.9		
Viewing Angle	60°		
Shutter Speed	1 / 60 (1/50) to 1 / 100,000 sec.		
Min Illumination	1 Lux		
Video Output	1.0 Vp-p. 75Ω		
BLC	AUTO		
White Balance	ATW		
■ Others			
Mobile Surveillance	iPad, iPod, iPhone, BlackBerry, Windows Mobile, Symbian & Android		
Remote Control	YES		
Motion Detection	YES		
Power	DC12V, 0.5A		
Operating Temperature	<b>0~40</b> °C		
Humidity	85%		
Minimum Web Browsing Requirements	<ul> <li>Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD</li> <li>256 MB RAM</li> <li>AGP graphics card, Direct Draw, 32MB RAM</li> <li>Windows 7, Vista &amp; XP, DirectX 9.0 or later</li> <li>Internet Explorer 7.x or later</li> </ul>		
Dimension (mm)**	152.5(L) x 115.2(W) x 40.2	2(H) (6.00" x 4.54" x 1.58")	
Shipping Weight	812g (1.79 lbs) including mounting bracket and power supply		
In/Out Door Use	Indoor		

\* The specifications are subject to change without notice.

\*\* Dimensional tolerance: (± 5mm)

## **Dimensions (mm)**

152.5 (L) x 115.2 (W) x 40.2 (H)



