Cyber Power

EXTENDED BATTERY MODULE SERIES



The battery module allows users to perform battery maintenance without interruption


Designed for data center and critical applications, the Extended Battery Module (EBM) Series can be used in conjunction with compatible UPS systems to provide prolonged system runtime during power interruption. The battery modules come with DC plug-and-play power connectors to allow for adding multiple EBMs. The products feature hot-swappable battery packs, allowing users to safely remove and replace battery packs without affecting connected loads.

SERIES FEATURES

- Rack/Tower Convertible Configurations
- Sealed Lead-acid Batteries
- Hot-swappable Batteries
- EBM Expansion Capability
- Metal Housing

PRODUCT CALLOUTS

- On-board Replaceable Fuse Cover
- 2. DC Output Connector
- 3. DC Input Connector



BPSE36V45ART2U/BPSE72V45ART2U

TECHNICAL SPECIFICATIONS

Model Name	BPSE36V45ART2U	BPSE72V45ART2U
General		
Nominal Output Voltage (Vdc)	36	72
Rated Output Current (A)	45	45
Battery		
Battery Type	Sealed Lead-acid	Sealed Lead-acid
Built-in Charger	No	No
Typical Recharge Time (Hours)	2 (Depends on Connected UPS)	2 (Depends on Connected UPS)
User-replaceable	Yes	Yes - Qualified Personnel Only
Hot-swappable	Yes	Yes
Replacement Battery Pack	RBP0068	RBP0071
Replacement Battery Pack Quantity (pcs)	2	2
Compatible UPS Models	OLS1000ERT2U, OLS1500ERT2U, OLS1000ERTXL2U, OLS1500ERTXL2U	OLS2000ERT2U, OLS3000ERT2U, OLS2000ERTXL2U, OLS3000ERTXL2U
Physical		
Form Factor	Rack/Tower	Rack/Tower
Physical Size		
Dimensions (WxHxD) (mm.)	438 x 88 x 430	438 x 88 x 610
Weight (kg.)	24.2	34.7
Installed Rack Height (U)	2	2
Environmental		
Operating Temperature (°C)	0 ~ 40	0 ~ 40
Operating Relative Humidity (Non-condensing) (%)	0 ~ 90	0 ~ 90
Certifications		
Certifications*	CE, EAC, LOA	CE, EAC, LOA
RoHS	Yes	Yes

^{*}Certifications may vary according to different regions. Visit www.cyberpower.com for more information.

#All specifications are subject to change without notice

