

# DIGITUS Professional PoE Injector, 802.3af

DN-95102  
EAN 4016032279303



**DIGITUS PoE Injector, 802.3af 10/100 Mbps Output max. 48V, 15.4W**

**Reduce cabling for Wireless APs, IP Phone and any PoE-ready device**

- Complies with the 802.3af PoE standard
- 48V output voltage, 15.4 Watt
- LAN(RJ45) input jack
- LAN(RJ45) output jack
- Connection: 10/100 Mbit/s
- Each output port has output current limited, short-circuit protection, complete Powered Device (PD) detection and classification

- Own consumption: 1,6W max
- Operating system independent, supports e.g. Windows, Mac OS, Linux and Sun
- Operating Temperature: 0 to 40°C
- Storage temperatur: -20 to 85°C

**Package contents**

- PoE Injector, 802.3af
- Quick installation guide
- Power cord

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	20	10.20	50.60	40.90	26.40	54,635.90
Packaging Unit Inside	1	0.51	9.00	19.50	12.00	2,106.00
Packaging Unit Single	1	0.51	9.00	19.50	12.00	2,106.00
Net single without Packaging	1	0.34	12.00	5.00	4.00	240.00



More images:

