

# DHL49-4K

## 49" UHD LCD Monitor



### Features:

- 4K ultra-HD resolution
- Industrial level DID LCD panel, suitable for extensive 7x24 continuous works
- High fidelity digital processing, brilliant and vivid video
- Built-in 3D COMB filter and 3D Noise Reduction
- 8ms fast response time, no image ghosting
- 16.7M color, display every details of video
- Brightness smart detection, power-saving
- Using Tamper-proof metal housing, no radiation
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Abundant interfaces HDMI, DVI, VGA, BNC, USB, support video loop

### Technical Specification

#### Model

Model	DHL49-4K
-------	----------

#### System

Diagonal	48.5"(16:9)
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance (Standard)	500 cd/㎡
Contrast	1100:1
Angle of view	178°/178°(vertical/horizontal)
Response time	8ms

#### Signals

Input	standard	VGA(D-Sub)×1, CVBS(BNC)×1, DVI-D×1, HDMI×2, RS232×1, USB multimedia×1
	optional	Audio×1, RJ45×1, HDCVI×1, SDI×1, DP×1
Output	Standard	Audio×1, RS232×1
	optional	DP×1

#### General

Consumption (Standard)	70W
Consumption (Standby)	≤1W





Power Supply	AC100~240V (+/-10%),50/60 Hz
Weight	18kg
Dimensions(no base)	1127.1×667.3×51.9mm
Work Environment	Temperature:0℃~50℃
	Humidity:20%~90%
VESA	300×300mm

#### Accessory

Standard	VGA cable, power cable
Optional	Pedestal, hanging bracket

**Dimensions(mm)**



AC 100 - 240V 1.2A 50/60 HZ AC IN	ON OFF											
	<input type="checkbox"/>											