

DH-NVR4208/4216/4232V-8P

8/16/32CH 2HDD 8PoE Vertical Network Video Recorder



Features

- > Up to 8/16/32 channel IP camera input
- > H.264/MJPEG dual codec decoding
- > Max 200Mbps incoming bandwidth
- > HDMI/VGA simultaneous video output
- > 8/16 channel synchronous realtime playback, GRID interface& smart search
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc.
- > ONVIF Version 2.4 conformance
- > 3D intelligent positioning with Dahua PTZ camera
- > Support 2 SATA HDDs up to 8TB, 3 USB
- > Support IPC UPnP, 8PoE ports
- > Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & Smart Phone(DMSS)

DH-NVR4208/4216/4232V-8P

Technical Specifications

| Model | DH-NVR4208V-8P | DH-NVR4216V-8P | DH-NVR4232V-8P |
|------------------------------------|---|----------------|----------------|
| System | | | |
| Main Processor | Dual-core embedded processor | | |
| Operating System | Embedded LINUX | | |
| Video& Audio | | | |
| IP Camera Input | 8 channel | 16 channel | 32 channel |
| Two-way Talk | 1 channel Input, 1 channel Output | | |
| Display | | | |
| Interface | 1 HDMI, 1 VGA | | |
| Resolution | 1920×1080, 1280×1024, 1280×720, 1024×768 | | |
| Display Split | 1/4/8/9 | 1/4/8/9/16 | 1/4/8/9/16 |
| OSD | Camera title, Time, Video loss, Camera lock, Motion detection, Recording | | |
| Recording | | | |
| Compression | H.264/MJPEG | | |
| Resolution | 5Mp(2560×1920)/3Mp(2048×1536)/1080P(1920×1080)/720P(1280×720)/D1 (704×576/704×480) &etc. | | |
| Record Rate | 200Mbps | | |
| Bit Rate | 48~ 8192kbps | | |
| Record Mode | Manual, Schedule(Regular(Continuous), MD, Alarm), Stop | | |
| Record Interval | 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec | | |
| Video Detection & Alarm | | | |
| Trigger Events | Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips | | |
| Video Detection | Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank | | |
| Alarm Input | 2 channel | | |
| Relay Output | 1 channel | | |
| Playback & Backup | | | |
| Sync Playback | 1/4/8 | 1/4/8/16 | 1/4/8/16 |
| Search Mode | Time/Date, Alarm, MD & Exact search (accurate to second), Smart search | | |
| Playback Function | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom | | |
| Backup Mode | USB Device/Network/Internal SATA burner/eSATA Device | | |
| Network | | | |
| Ethernet | 1 RJ-45 port (10/100/1000Mbps) | | |
| PoE | 8 ports (IEEE802.3af/at) | | |
| Network Function | HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.) | | |
| Max. User Access | 128 users | | |

DH-NVR4208/4216/4232V-8P

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2014 Dahua Technology Co., Ltd.