

DS-D6032FL-B Indoor Wall-Mounted Digital Signage

The digital signage is used to broadcast information, release news, advertise products, etc., which is widely applicable to industry of entertainment, finance, traffic, etc.



Feature and Function


- **Metallic Appearance**
Features in thin body and ultra-narrow boarder with integrative quadrilateral design, and supports horizontal and vertical installation.
- **Exquisite Image**
Industrial A+ panel, auto-coloring and image-enhancing engine.
- **Variable Materials**
Supports static and dynamic materials, including the pictures, audio, video, scrolling subtitle, PDF, webpages, live video, number calling, pop-up pictures, etc.
- **Flexible Program Schedule**
 - Supports free schedule and district display of multiple materials.
 - Supports variable display modes: display by day, display by week, custom display, etc.
- **Centralized Management**
 - Remotely controls and manages one screen or more screens, such as timed startup/shutdown, quick startup/shutdown, brightness/volume timed adjustment, and screenshot preview.
 - Remotely releases programs and updates local (USB) programs.
- **Organization Permission**
 - 5-level organization is available for managing materials, programs, terminals, and users.
 - Supports creating custom users, and allocating permission for users according to user level.
- **Multiple Security Safeguards**
 - 3-level check of materials, programs and schedules to prevent mistake release.
 - Encryption of data in storage and transmission to prevent data tampering.
 - Screensaver to secure the security of broadcast contents.



Specification

Model		DS-D6032FL-B
Display	Screen size	31.51 inch
	Active display area	698.4(H) × 392.85(V) mm (27.50 × 15.47 inch)
	Backlight	Direct illumination-type LED backlight
	Pixel pitch	0.12125 (H) × 0.36375 (V) mm
	Resolution	1920 × 1080@60 Hz
	Brightness	350 cd/m ²
	Viewing angle	Horizontal: 178°, vertical: 178°
	Color depth	8 bit
	Contrast ratio	1200: 1
	Response time	8 ms
	Refresh rate	60 Hz
	Color gamut	75% NTSC
	Reliability	7 × 24 h
Interface	Video & audio input	1 × AUDIO IN
	Video & audio output	1 × AUDIO OUT 2 × built-in speaker, 8 Ω 5 W
	Network interface	1 × LAN, Wi-Fi 2.4 G
	Data transmission interface	2 × USB 2.0 interface, 1 × TF Card Note: The USB interface only supports for low power equipment, such as the keyboard or mouse.
Built-in system	Processor	4-core Cortex-A17, main screen 1.8 GHz
	Memory	2 GB
	Built-in storage	8 GB EMMC, TF 32 GB, Max. 128 GB
	Operation system	Android 6.0.1
General	Material type	DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, TS, FLV, WEBM, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF, MXMF, RTTTL, RTX, OTA, IMY, JPG, JPEG, BMP, GIF, PNG
	Power supply	100 to 240 VAC, 50/60 ± 3 Hz
	Power consumption	≤ 60 W
	Standby consumption	≤ 10 W
	Working temperature	0 °C to 40 °C (32 °F to 104 °F)
	Working humidity	10 % to 80 % RH
	Storage temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Storage humidity	10 % to 80 % RH
	Product dimensions	748.31(W) × 447.11(H) × 55.9(D) mm (without wall-mounted backboard) (29.46 × 17.60 × 2.20 inch) 748.31(W) × 447.11(H) × 71.4(D) mm (with wall-mounted backboard) (29.46 × 17.60 × 2.81 inch)
	Package dimensions	904(W) × 643(H) × 210(D) mm (35.59 × 25.31 × 8.27 inch)
	Gross weight	16.1 kg (35.49 lb.)
	Net weight	15.1 kg (33.29 lb.)
	Accessory	Power cord, Remote control, Battery × 2, Expansion bolt, Installation guide, LOGO

Physical Interface




No.	Interface	Description	No.	Interface	Description
1	SWITCH	Power switch	2	100-240V~	Power supply
3	LAN	LAN network interface	4	USB	USB 2.0 interface
5	USB	USB 2.0 interface	6	AUDIO IN	Audio input
7	AUDIO OUT	Audio output	8	TF	TF card slot


Available Model

DS-D6032FL-B

Dimension (unit: mm)



Typical Application



Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com