

DS-KH8350-TE1 Video Intercom Network Indoor Station


HIKVISION



Key Feature

- Premium tempered glass
- Aerospace-grade aluminum
- New UI V2.0: User friendly design
- 7-inch colorful touch screen with resolution 1024 × 600
- 8.6 mm Ultra-slim design
- Reddot award 2017 winner
- Standard PoE
- Support capture while video calling
- Remote unlocking via the client software or the mobile client
- Views live videos of door stations and linked cameras

Typical Application



Approval

| | |
|-------------|---|
| CE-EMC | a. EN 55032:2015 b. EN 61000-3-2:2014 c. EN 61000-3-3:2013 d. EN 50130-4:2011 +A1:2014 |
| CE-LVD | EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013 |
| CB | IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013 |
| FCC-SDOC | 47 CFR Part 15, Subpart B |
| C-TICK(EMC) | AS/NZS CISPR 32:2015 |
| UL | UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07, Information Technology Equipment – Safety – Part 1: General Requirements |
| IC(EMC) | ICES-003:Issue 6 |
| ROHS | 2011/65/EU |
| REACH | Regulation (EC) No 1907/2006 |
| WEEE | 2012/19/EU |


Specification

| System parameters | |
|----------------------------|---|
| Memory | 128 MB |
| Flash | 32 MB |
| Operation system | Embedded Linux operation system |
| Display parameters | |
| Display screen | 7-inch colorful TFT screen |
| Display resolution | 1024 × 600 |
| Operation method | Capacitive touch screen |
| Audio parameters | |
| Audio input | Built-in omnidirectional microphone |
| Audio output | Built-in loudspeaker |
| Audio compression standard | G.711 U |
| Audio compression rate | 64 Kbps |
| Audio quality | Noise suppression and echo cancellation |
| Network parameters | |
| Wired network | 10/100 Mbps self-adaptive |
| Network protocol | TCP/IP, SIP, RTSP |
| Network interface | 1 RJ-45 10/100 Mbps self-adaptive |
| Alarm input | 8-ch alarm inputs |
| I/O output | 2 |
| TF card | Max to 32 G, SD 2.0 or lower version |
| RS485 | Supported |
| Performance | |
| Linked IPC | Max. 16 |
| Linked indoor extensions | Max. 5 |
| Notices | Max. 200 |
| Captures | Max. 2M |
| General | |
| Power supply | IEEE802.3af, standard PoE 12 VDC/1 A |
| Power supply via detector | 12 V, 200 mA |
| Power consumption | ≤ 7 W |
| Working temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| Working humidity | 10% to 90% |
| Dimensions | 180 mm × 140 mm × 22.4 mm (7.09" × 5.51" × 0.88") |
| Weight | 786 g (with packaging) 600 g (without packaging) |
| Certification | FCC, IC, CE, C-TICK, ROHS, REACH, WEEE, UL, CB, RCM |


Available Model

DS-KH8350-TE1

Dimension




Appearance and Interfaces



Accessory

Installation



Surface Mounting



Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com